



**NOTES:**

- 1) MATERIAL: 6061-T6/T651/T6510/T6511/T62 ALUMINUM BAR  
PER QQ-A-225/8 OR AMS-QQ-A-225/8 (OR AMS 4117/4128/4115/4116)  
OR QQ-A-200/8 OR AMS-QQ-A-200/8 (OR AMS 4160)  
OR ASTM B211 OR ASTM B221  
REF DART SPEC M6061T6B
- 2) FINISH: ANODIZE BLACK PER MIL-A-8625F TYPE I OR IB OR IC OR II OR IIB CLASS 2
- 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
- 4) UNITS: INCHES UNLESS OTHERWISE NOTED
- 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
- 6) IDENTIFICATION: IDENTIFY PER QSI 044 6.1
- 7) WEIGHT: 0.94 lbs
- 8) UNDEFINED FEATURES CONTROLLED BY CAD FILE D5069-1 REV. A.SLDPRT

RELEASED  
2018-01-08  
EON 17-793

APPROVED

A	NEW ISSUE	RF	17.07.24
REV.	DESCRIPTION		DATE
DESIGN	RF	<b>DART AEROSPACE USA, INC.</b> EUGENE, OR	
DRAWN	RF		
CHECKED	WK	DRAWING NO.	REV. A
MFG. APPR.	RQ	D5069	SHEET 1 OF 1
APPROVED	HS	TITLE	SCALE
DE APPR.	DS	HARDPOINT ADAPTER	NTS
DATE	17.07.24	<b>COPYRIGHT © 2017 BY DART AEROSPACE USA, INC.</b> THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE USA, INC.	